

Key **Features**


- EPEAT Gold Certification with 20% better power efficiency than the previous generation.
- Integrated ViewSonic Education Software empowers teachers and boosts learning outcomes.
- EDLA-certified Android 14 unlocks Google Play Store access for a world of apps.
- Quad-core CPU and microSD port deliver fast performance with expandable storage.
- Dual USB-C ports power fast transfers, reliable charging, and effortless connectivity.



Product **Description**

Start your EdTech journey right with the ViewBoard IFP34 Series, designed with enhanced writing functionality and optimized power efficiency to meet the needs of K12 and higher education. Powered by EDLA-certified Android 14, it offers a smooth, secure user experience with full access to the Play Store for endless educational and productivity apps.

Integrated ViewSonic Education Software takes it even further, adding powerful tools for digital whiteboarding, wireless casting, and centralized device management. Together, these features empower educators to create engaging, interactive learning environments, all while simplifying classroom workflows.



Visit Us

www.viewsonic.com

.33 PIVI VIEWSOII	ic viewboard iFP6554 Enterprise Device Lic
DISPLAY	05"
Panel Size:	65" TET LCD Module with DLED Packlight
Panel Type: Display Area (mm):	TFT LCD Module with DLED Backlight. 1428.48(H) x 816.02(V)
Aspect Ratio:	16:9
Resolution:	UHD 3840x2160(Pixels)
Colors:	1.07B colors
Brightness:	350 nits
Contrast Ratio:	5000:1 (max. with DCR enabled)
Response Time:	8ms
Viewing Angles:	H=178, V=178
Backlight Life:	50,000 Hours (8 hours of use per day)
Surface Treatment:	Hardness: 9H Pencil hardness with Anti-glare coating
Orientation:	Landscape
PLATFORM	
Processor:	Quad-core
RAM: Storage:	8GB DDR4 128 GB
TOUCH	120 GD
Type/ Tech:	Ultra Fine Touch Technology
Touch Resolution:	32767 x 32767
Touch Point:	40 points touch
Palm Rejection:	Yes
INPUT	
HDMI:	x3 (Front x1: HDMI2.1 4K@60Hz/HDCP 2.3/CEC; Rear x 2:HDMI2.1 4K@60Hz/HDCP 2.3/CEC/ARC for HDMI 2)
RGB / VGA:	х1
DisplayPort:	х1
Audio:	x1
RS232: SD/SDHC:	x1
OPS:	x1 x1 (Optional Intel Standard OPS)
WiFi:	x1 (Optional VB-WIFI-004/VB-WIFI-006/VSB-050)
OUTPUT	
HDMI:	HDMI 2.0 x1
Audio:	x1
SPDIF:	x1
LAN	
RJ45:	x2
USB	
Type A:	USB3.2 Gen 1 x 4 (Front x 2; Rear x 2) USB 2.0x1 (Rear)
Type B:	USB 3.0 x2 (Rear x1 + Front x1)
Type C:	Front*1 [PD65W (15W with OPS, 65W without OPS)+ DP1.2 + Data + 10M/100M sharing)] Rear*1 [PD15W + DP1.2 + Data + 10M/100M sharing]
SPEAKERS	
20W x 2	
TOP CAMERA PLATE Yes	
EMBEDDED OS	
Android 14 EDLA	
BUNDLE SOFTWARE	
Basic Annotation Software:	myViewBoard
Pro Annotation Software:	myViewBoard for Windows (Embedded in optional Windows Slot-in PC)
Wireless Presentation:	AirSync
Device Management:	Manager
ViewSonic Launcher:	Yes
SPECIAL FEATURES	
All-in-one USB port:	(combine slot-in PC/Android/HDMI USB port) Front "SmartPort™ USB" to all channels.
Simple LAN sharing between IFP and slot-in device:	10/100M for Android & Slot-in PC
Light Sensor:	Yes
POWER	
Voltage:	100-240V AC
Consumption:	On:78.26W ; Off: ≤ 0.5W
ERGONOMICS	0001100
Wall Mount (VESA®):	600*400
OPERATING CONDITIONS Temperature (° C):	0°C to 40°C

DIMENSIONS (W X H X D)

Physical (inch / mm): 58.4 x 35.1 x 3.45 (in.) / 1482.2 x 891.4 x 87.7 (mm)

Packaging (inch / mm): 64.56 x 39.76 x 7.28 (in.) / 1640 x 1010 x 185(mm)

WEIGHT Net (lb / kg):

Net (lb / kg): 80.25lb / 36.4kg Gross (lb / kg): 101.19lb / 45.9kg

REGULATIONS

FCC/ICES003, EPEAT, CE EMC, LVD or CB, RoHS Green BOM, & RoHS DoC, ErP, REACH SVHC List, & DoC, EEL, WEEE, BSMI,BIS

PACKAGE CONTENTS

1. 3m power cord by ship area 2. Remote control with AAA battery 3. 3m touch USB cable 4. Passive pen x 2 5. Quick Start Guide + Compliance statement 6. RS232 adapter 7. Clamp x 5 8. Camera Plate 9. Screw x 8 (camera 2+2, wall mount 4) 10. HDMI cable 3m

COMPATIBLE SLOT-IN PC

VPC3X, VPCF5-2A, VPCF5, VPC-A31-O1

20% ~ 80% RH non-condensing

Humidity: