


Technical Specifications



- a: Projection distance
- b: Lens centre to the higher edge of the screen
- c: Lens centre to the lower edge of the screen

IMAGE SIZE 16:10 (FROM PROJECTOR'S END)				
Screen size (diagonal)	Projection distance (a)		Screen height (cm)	
	Wide (m)	Tele (m)	b (top)	c (bottom)
30" (0.8m)	0.9	1.1	38	3
40" (1.0m)	1.2	1.5	50	4
50" (1.3m)	1.6	1.9	63	5
60" (1.5m)	1.9	2.3	75	6
100" (2.5m)	3.2	3.8	125	10
200" (5.1m)	6.4	7.7	250	19
300" (7.6m)	9.6	11.5	375	29

IMAGE SIZE 4:3 (FROM PROJECTOR'S END)				
Screen size (diagonal)	Projection distance (a)		Screen height (cm)	
	Wide (m)	Tele (m)	b (top)	c (bottom)
30" (0.8m)	1.0	1.3	42	3
40" (1.0m)	1.4	1.7	57	4
50" (1.3m)	1.8	2.1	71	5
60" (1.5m)	2.1	2.6	85	7
100" (2.5m)	3.6	4.3	142	11
200" (5.1m)	7.2	8.7	283	22
300" (7.6m)	10.9	13.1	425	33



OPTICAL	
LCD panel	0.59" aspect ratio 16:10
Resolution	WXGA (1280 x 800)
White light output (brightness)	3700 Lumens (Normal) / 3034 Lumens (Eco1) / 2479 (Eco 2)
Colour light output (colour brightness)	3700 Lumens (Normal) / 3034 Lumens (Eco1) / 2479 (Eco2)
Contrast ratio	10000:1
Lens	Manual focus, manual zoom x 1.2
Lamp wattage	225W
Lamp life*	5000 hours (Normal) / 8000 hours (Eco1) / 10000 hours (Eco2)
Diagonal display size	30~300" (76~762cm)
Number of colours	16.7 million
Keystone	Fixed 13:1 upward shift, Normal at + 10.3° ~ 8.6° projection angle
Focus distance	0.9 ~ 9.6m (Wide), 1.1~ 11.6m (Tele)
Distance to width ratio	1.5 (Wide), 1.8 (Tele)

COMPATIBILITY	
Computer compatibility	IBM Compatible VGA, SVGA, XGA, WXGA WXGA+ / SXGA/SXGA+ / UXGA (compressed) MAC16"
Composite / S-Video	NTSC, PAL, SECAM, PAL-M, PAL-N, NTSC4.43
Component video	525i(480i), 525p(480p), 625i(576i), 1125i(1080i@50/60), 750p(720p@50/60), 1125p(1080p@50/60)
HDMI video	Video signals: 525i(480i), 525p(480p), 625i(576i), 1125i(1080i@50/60), 750p(720p@50/60), 1125p(1080p@50/60)
Plug & play	DDC2B (VESA)

FEATURES	
Speakers	16W x 1 (mono)
Basic functions	Freeze, magnifying, blank, auto adjustment, search, page up & down (for USB mouse function), auto signal search, auto eco mode
Picture adjustments	Aspect selection (video, data, HDMI), equalizing digital gamma correction, equalizing colour temperature adjustment, 2-3 pull down for NTSC, mirror reverse image, up-side down image, progressive scan, noise reduction, overscan
Digital keystone correction	Horizontal & vertical: ±30 degrees
Advanced features	Accentualizer, HDCR, audio pass through, cloning, auto signal search, perfect fit, PC less presentation, ECO -1, ECO -2, MyScreen, My Memory, My Button, My Text, My Source, picture mode (normal, cinema, dynamic, blackboard, whiteboard greenboard, photo), daytime mode, Input source naming (English), resolution setting, template, Closed Caption (for NTSC & component 480i only), audio pass through, frame lock, audio ports assign, cloning, drawing function (optional wireless pen tablet TB-1 is necessary), eco mode (normal, eco, intelligent eco, saver), iOS Connectivity, ImageCare™, easy schedule function
Outward	Easy lamp replace from top, easy access air filter
Power on & off	Direct on, auto off
Security systems	PIN Security Lock, MyScreen Password Lock, transition detector, My Text Password Lock, key lock (key pad, remote control)
Network	Projector monitoring (Wired LAN), control from a remote location (Wired LAN), E-mail alerts (Wired LAN), mirroring the PC Screen (uses LiveViewer software) infrastructure mode (wireless LAN), Simple Access Point (SoftAP), SNMP Management (SNMP)
OSD languages	English, French, German, Spanish, Italian, Norwegian, Dutch, Japanese, Portuguese, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkish, Arabic, Persian, Czech, Danish, Hungarian, Romanian, Slovenian, Croatian, Greek, Lithuanian, Estonian, Latvian, Thai, Portuguese (Brazil), Indonesian, Vietnamese

CONNECTIONS	
Digital input	HDMI (HDCP compliant) x 2
Computer input	Mini-D-Sub 15-pin connector x 2
Monitor output	Mini-D-Sub 15-pin connector x 1
Video input	RCA connector x 1
Audio input	3.5 mm stereo mini connector x2 RCA jack(L, R) x1
Audio output	3.5mm stereo mini connector x 1
USB Type A	USB type A x 2 (PC less) presentation or wireless adapter
USB Type B	USB type B x 1 (USB display, or USB mouse control)
Wired network	1 x RJ-45
Wireless network	IEEE801.11b/g/n ready (optional USB wireless adapter required)
Control	1 x 9-pin D-sub for RS-232C control

POWER	
Power supply	AC 100-120V / AC 220-240V, auto switching
Power consumption / standby	310W / <0.5W (AC 220-240V)

PHYSICAL	
Dimensions (W x H x D)	320 x 85 x 245mm (excluding feet and extrusions)
Weight	3.0Kg
Noise level	37dB (Normal) / 32dB (Eco1) / 29dB (Eco2)
Air filter*	Unwoven fabric, replacement cycle: 5000hr (varies according to usage environment)

MISCELLANEOUS	
Indicator lights (lamp, temp, power), ceiling mount image, rear projection image, serial number label on side, MAC address label on side, MAC PC support	

CERTIFICATION	
UL60950-1/CUL, FCC PART 15 SUBPART B CLASS B, CE MARKING: EN61000-3-2, EN61000-3-3, EN55022 (CLASS B), EN55024 (EMC DIRECTIVE), EN60950-1 (LOW VOLTAGE DIRECTIVE), WEEE, ROHS, ERP (LOT6) COMPLIANT, GS MARK, C-TICK CLASS B (STANDARD FOR AUSTRALIA/NEW ZEALAND.)	

ACCESSORIES SUPPLIED	
Power cable, computer cable, remote control with batteries, lens cover and cap, adapter cover (for USB wireless adapter), security label, user's manual CD, user's manual book, application CD	

OPTIONAL ACCESSORIES	
Replacement lamp	DT01481
USB wireless adaptor	USB-WL-11N
Remote control	HLO3031

Warranty	
Projector / lamp	3 Years / 6 Months** (for education and extended warranties please contact your local dealer.)

*The stated lamp and filter life refers to the average life expected in ideal operating conditions with usage in accordance with the manual. The majority of, but not all lamps and filters should achieve this figure. **Where a lamp fails within warranty and a replacement lamp is taken, the warranty for the replacement lamp will be a maximum of 6 months (dependent on warranty hours stated). HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC. AMX and the AMX logo, and Device Discovery are all registered trademarks of AMX. Crestron® and RoomView™ are registered trademarks or trademark of Crestron Electronics, Inc. The specification above and photography is for reference only and may be subject to change.